

MBX Mini



Good things come in small packages

Small is the new mighty.


Bring your deployments to life with the versatility of the MBX Mini. It's just as brilliant as any other MBX device we have to offer. So connect your devices to the PoE enabled LAN ports to provide network simplicity as well as IEEE 802.1X port authentication. This MBX Mini has the power to achieve it all.



Keep your connection flowing in whatever deployment that you're immersed in and deliver more power and redundancy with THREE power input options: DC Source A, DC Source B, and a terminal block.


One. Two. Three. Four.

We know fast connections are critical to achieving great things. Its dual-band Wi-Fi and 5G capabilities ensure you experience the fastest available network. If the dual embedded cellular WANs are not enough, the MBX Mini can be expanded to FOUR cellular WANs by simply connecting it to our MAX Adapters via the dual USB ports.



Making hard to manage feel like hardly managing.

With this FusionSIM-ready router, you can say goodbye to switching and managing multiple SIMs via the router. FusionSIM offers remote provisioning of SIM profiles from anywhere in the world. Managing made easy, ready when you are!



Specifications

WAN Interface	2x Embedded Cellular Modems with Redundant SIM Slots 2x GE 2x USB 2.0 Interface	Power Output	Up to 6x 802.3at PoE ²
LAN Interface	4x GE	Power Consumption	45 W (max.)
Wi-Fi Interface	802.11ac/a/b/g/n, 1166 Mbps 2x2MIMO Wi-Fi WAN and/or AP Simultaneous Dual-Band	Dimension	7.32 x 8.05 x 1.61 inches 186 x 204.5 x 41 mm
Router Throughput	2.5 Gbps	Weight	4.19 pounds / 1.9 kg
SpeedFusion VPN Throughput - No Encryption - 256-bit AES	600 Mbps 500 Mbps	Operating Temperature	-40°– 149°F / -40°– 65°C
5G Cellular Data Rate (Downlink/Uplink)	5G: 3.4 Gbps / 900 Mbps LTE CAT-20: 1.6 Gbps / 200 Mbps	Humidity	15% – 95% (non-condensing)
SpeedFusion features	Hot Failover, Smoothing, Bandwidth Bonding, Bandwidth Overflow	Certifications	FCC, CE, RoHS, E-Mark, PTCRB Shock and Vibration Resistance: EN 61373:1999 IEC 61373:1999 Railway Applications: EN 50155 Electromagnetic Compatibility: EN 61000
Number of SpeedFusion VPN Peers	3/20 ¹	Package Content ³	MBX Mini, PSU 180W (ACW-630), 4x Dual-Band Wi-Fi Antennas (ACW-341) 1x QMA to SMA Adapter (for GPS), 1x GPS Antenna (ACW-232), Power cord, 1 Pair of Ear L-Mounts kit (ACW-756), Screw set of Ear L-Mounts kit, 3pin Terminal Block Connector (Ignition Sense), 4pin Terminal Block Connector (Power Supply), Rubber Foot Pad set
Recommended Users	50-500	Warranty	1-Year Limited Warranty
Antenna Connectors	8x QMA Cellular Antenna Connectors 1x QMA GPS Antenna Connector 4x RP-SMA Wi-Fi Antenna Connectors		
Power Input	AC Adapter: AC Input 100V-240V / DC Output 12V DC Jack / Terminal Block: 12-56 V		

¹ Requires a license to increase the maximum number of SpeedFusion VPN Peers. Several options are available based on the model 5, 10 or 20 peers (PVN-LC-05, PVN-LC-10, PVN-LC-20). ² 2x 54V DC input is needed for all 6x LAN/WAN ports to provide 802.3at PoE. Plugging in 1x 54V DC input will result in 4x LAN ports providing 802.3at PoE. PoE output on WAN ports will be supported with Firmware 8.4.0 or above. ⁴ Cellular antennas not included. To enhance the MBX Mini, Mobility and Maritime antennas are recommended.

Ordering information

Product Code	Embedded Modem(s)	Regions	5G Bands	LTE Bands
MAX-MBX-MINI-5GD-T	2x 5G	Global	5G (NSA) Sub 6Ghz: n1, n2, n3, n5, n7, n8, n12, n20, n28, n38, n41, n66, n71, n77, n78, n79	B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B32, B34, B38, B39, B40, B41, B42, B46, B48, B66, B71
MAX-MBX-MINI-5GH-T	2x 5G	Global*	5G (NSA) Sub 6Ghz: n1, n2, n3, n5, n7, n8, n12, n20, n25, n28, n38, n40, n41, n66, n71, n77, n78, n79	B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B32, B34, B38, B39, B40, B41, B42, B46, B48, B66, B71
MAX-MBX-MINI-5GN-T	2x 5G	Global	5G (NSA & SA) Sub 6Ghz: n1, n2, n3, n5, n7, n8, n12, n13, n14, n18, n20, n25, n26, n28, n29, n30, n38, n40, n41, n48, n66, n70, n71, n75, n76, n77, n78, n79	B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B32, B34, B38, B39, B40, B41, B42, B43, B46, B48, B66, B71

* US Carrier Certifications(: AT&T, FirstNet, US Cellular, Verizon (C-Band).

Feature Add-on

Product Code	Description
PVN-LC-05	Up to 5 SpeedFusion Bonding License Key for MBX Mini
PVN-LC-10	Up to 10 SpeedFusion Bonding License Key for MBX Mini
PVN-LC-20	Up to 20 SpeedFusion Bonding License Key for MBX Mini